



& ASSOCIATES, INC.

TRF115 Thermostat

- Rain Tight
- Temperature Control
- NEMA 4X
- Line Sensing



Description

The **TRF115** thermostat is designed for use as a line sensing control for pipes, vessels and other types of electric heat tracing applications. Suitable in agricultural, industrial and commercial environments.

Features

- Rugged weather resistant enclosure made of corrosion resistant materials for long life.
- Stainless steel remote bulb provides rapid response to temperature change.
- Large, readily visible dial with 0°F - 120°F temperature range.
- Multi-positional mounting offers flexibility in either new or existing installations.
- One control for both heating and cooling applications.



TAD & Associates, Inc.
P.O. Box 2170
Canyon Lake, Texas 78133

Phone: 830.964.4435
Fax: 830.964.4493
<http://www.tad-associates.com>



TAD & ASSOCIATES, INC.

TRF115 Thermostat

Characteristics

Type	Range	Differential	Bulb Size	Capillary Length	Shipping Weight
SPDT	0°F - 120°F	3°F	2 5/16" x 5/16"	5 Feet	1.0 Lbs

Mechanical Data

⚠ Electrical Ratings

	120VAC	240VAC	277VAC	480VAC
Full Load Amps	16.0	12.0	10.0	—
Locked Rotor Amps	80.0	60.0	50.0	—
Non-Inductive Resistive Load Amps	25.0	25.0	22.0	5.0

Installation

- Multi-positional mounting meets new or existing wiring needs.
- Insulated enclosure.
- All mounting holes are exterior to the enclosure.
- Easily removable knockouts in sides and top of enclosure.
- Large wiring compartment with watertight cover separated from thermostat compartment.
- May be cord or conduit connected.
- Pigtail leads for rapid, positive, electrical connection.

Applications

- Constant Wattage Heater Cables
- Self Limiting Heater Cables
- Mineral Insulated Heater Cables

